

(800) 225-2569

## **Kerryliquid** Church Candle Fuel

# **Material Safety Data Sheet**

# SECTION 1 PRODUCT AND COMPANY IDENTIFICATION

Trade name KerryLiquid

Use Church Candle Fuel

Manufacturer/Supplier CM ALMY

Address 3 American Lane, Greenwich, CT 06836

Emergency Telephone CHEMTREC North America Transportation Emergency (24-hr) (800) 424-9300

CHEMTREC World Wide (703) 527-3887

MSDS and Product Information (9 AM – 6 PM ET)

E-mail address almyaccess@almy.com

# **SECTION 2 HAZARDS IDENTIFICATION**

**Emergency Overview** 

Appearance water-clear oily liquid

**Odour** Hydrocarbons

Precautions CAUTION! MAY CAUSE EYE OR SKIN IRRITATION. Avoid contact with skin, eyes

and clothing. Wash thoroughly after handling.

**Environmental** Low toxicity to aquatic organisms such as bacteria, algae, protozoa and fish. Normal

**precautions** paraffins are removed by volatilization, sorption to sediments/soils and biodegradation.

**Potential Health Effects** 

Eyes Irritating to eyes.

Skin May cause skin irritation and/or dermatitis. High standards of skin care and personal

hygiene should be exercised at all times.

Inhalation May cause headache and dizziness.

**Ingestion** Aspiration hazard if swallowed - can enter lungs and cause damage.

(See Section 11 for Toxicological Information)



### SECTION 3 COMPOSITION AND INFORMATION ON INGREDIENTS

 Components
 CAS-No.
 Weight %

 Alkanes, C14-16
 90622-46-1
 100

See Section 8 for Exposure Guidelines and Section 15 for Regulatory Classifications.

# **SECTION 4 FIRST AID MEASURES**

Eye contact Rinse immediately with plenty of water for at least 15 minutes. If eye irritation persists,

consult a specialist.

**Skin contact** In case of contact, immediately flush skin with plenty of water for at least 15 minutes

while removing contaminated clothing and shoes.

**Inhalation** Remove to fresh air. If breathing is irregular or stopped, administer artificial respiration.

Call a physician immediately.

**Ingestion** Do NOT induce vomiting. Consult a physician.

### SECTION 5 FIRE-FIGHTING MEASURES

### **FLAMMABLE PROPERTIES**

Flash point 118 °C PM 244 °F

Autoignition 204 °C 400 °F

temperature

Flammable limits in Lower explosion limit: 0.5%(V) air % by volume Upper explosion limit: 4.7%(V)

Fire and explosion NFPA Class IIIB combustible liquid.

**Extinguishing media** Water spray or fog, foam, dry chemical, CO2.

**Fire fighting** In the event of fire, wear self-contained breathing apparatus.

instructions

Further information Keep containers and surroundings cool with water spray.

Page 2 of 7



### SECTION 6 ACCIDENTAL RELEASE MEASURES

case of spill or leak

Steps to be taken in Evacuate the area and eliminate all sources of ignition. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

### SECTION 7 HANDLING AND STORAGE

**Safe handling advice** Ensure all equipment is electrically grounded before beginning transfer operations.

Storage/Transport **Ambient** 

pressure

Load/Unload temperature

Ambient, above freezing point. (Product will freeze at 4 C)

### SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

#### **ENGINEERING MEASURES**

Air contaminant levels should be controlled below the PEL or TLV for this product (see Exposure Guidelines).

#### PERSONAL PROTECTIVE EQUIPMENT

Eyes Chemical resistant goggles must be worn. Face-shield

**Skin** Wear suitable protective clothing, gloves and eye/face protection.

Inhalation Respiratory protection is normally not required except in emergencies or when conditions

cause excessive airborne levels of mists or vapors. Use NIOSH approved respiratory

protection.

### **EXPOSURE GUIDELINES**

Components Exposure limit(s)

> Contains no substances with occupational exposure limit values. SASOL North America recommends an internal limit of 5 mg/m3 (8-hour TWA) for exposure to mists of this

product.

PEL= Permissible Exposure Limits TWA= Time Weighted Average (8 hr.) TLV= Threshold Limit Value Short Term Exposure Limit (15 min.) STFI = Workplace Environmental Exposure Level **Excursion Limit** WEEL=



### SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance oily liquid

Colour water clear

**Odour** Hydrocarbons

Form liquid

**Boiling point/boiling** 

248 - 284 °C 478 - 544 °F

range

Vapour pressure < 0.1 mm Hg @ 20 °C API Calculation

Vapour density 7.1

Solubility (water) negligible

> Viscosity 2.3 - 2.5 cSt @ 40 °C

Melting point/range 4 °C 39 °F (Freeze pt.)

Specific gravity 0.768 @ 16 °C

# **SECTION 10 STABILITY AND REACTIVITY**

**Conditions to avoid** Keep away from heat and sources of ignition.

Hazardous decomposition

products

Store away from other Oxidizing agents

materials.

Hazardous Stable

polymerization

# **SECTION 11 TOXICOLOGICAL INFORMATION**

Primary irritation (rabbit): 1 hours 5.7 (Maximum score is 110.) (unwashed eyes)

Hazardous gases and vapors produced in fire are oxides of carbon.

Primary irritation (rabbit): 1 hours 6 (Maximum score is 110.) (washed eyes)

**Skin** Primary irritation (rabbit): 4.4 (Maximum score is 8.0.)

Acute dermal LD50 (rabbit): > 2,000 mg/kg



**Inhalation** Acute 4 hours LC50 (rat): > 5.8 mg/l

Ingestion Acute oral LD50 (rat): > 5,000 mg/kg

**CARCINOGENICITY** 

Contains no ingredient listed as a carcinogen

### SECTION 12 ECOLOGICAL INFORMATION

Aquatic toxicity Low toxicity to aquatic organisms such as bacteria, algae, protozoa and fish.

(Pimephales promelas (fathead minnow)):

Considered relatively non-toxic as demonstrated by a no significant effect at any concentration of the water soluble fraction of C13-C16 normal paraffins to fathead

minnows and water-fleas.

Biodegradation Normal paraffins are removed by volatilization, sorption to sediments/soils and

biodegradation.

## **SECTION 13 DISPOSAL CONSIDERATIONS**

Waste Code Any unused product or empty containers may be disposed of as non-hazardous in

accordance with state and federal requirements. Re-evaluation of the product may be required by the user at the time of disposal, since the product uses, transformations, mixtures, contamination, and spillage may change the classification. If the resulting material is determined to be hazardous, please dispose in accordance with state and

federal (40 CFR 262) hazardous waste regulations.

**Disposal methods** Dispose of only in accordance with local, state, and federal regulations.

Empty containers Empty containers retain product residue (liquid and/or vapor) and can be dangerous. DO

NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION; THEY MAY EXPLODE AND CAUSE INJURY OR DEATH. Empty drums should be completely drained, triple-rinsed, properly bunged and

promptly returned to a drum reconditioner, or properly disposed.

### SECTION 14 TRANSPORT INFORMATION

**DOT** not regulated

IATA not regulated

IMDG not regulated



## SECTION 15 REGULATORY INFORMATION

### **U.S. FEDERAL REGULATIONS**

**OSHA Hazards** 

Non-hazardous substance

**TSCA Inventory Listing** 

<u>CAS-No.</u>

Alkanes, C14-16 90622-46-1

**SARA 302 Status** 

Components CAS-No. Weight %

Contains no chemicals subject to SARA 302 reporting.

SARA 311/312 Classification

Non-hazardous substance

**SARA 313 Chemical** 

Components CAS-No. Weight %

SARA 313: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

**CERCLA Hazardous Substance** 

Components Reportable Quantity Weight %

none

### INTERNATIONAL REGULATIONS

### Workplace Hazardous Materials Information System (WHMIS) Classification

WHMIS hazardous composition: No ingredients are hazardous according to the CPR criteria.

This product contains one or several components listed in the Canadian NDSL list.

### **European Union**

Classification and labelling according to Directive 67/548/EEC.

Xn: Harmful

R65 Harmful: may cause lung damage if swallowed.

### Australian Inventory of Chemical Substances (AICS) Listing

Listed



Japanese Minister of International Trade and Industry (MITI) Inventory Listing
Listed

Canadian Domestic Substance List (DSL) Inventory Listing

Not listed

**European Inventory of Existing Commercial Chemical Substances (EINECS) Listing** 

Listed

**Philippines Inventory List (PICCS)** 

Listed

**Korean Inventory List** 

Listed

**China Inventory List** 

Listed

### **STATE REGULATIONS**

California Prop. 65
Components

CAS-No.

none

### **SECTION 16 OTHER INFORMATION**

### **HAZARD RATINGS**

	<u>Health</u>	<u>Flammability</u>	Reactivity
HMIS	1	1	0
NFPA	1	1	0

THE DATA AND INFORMATION CONTAINED HEREIN ARE BEING FURNISHED FOR INFORMATIONAL PURPOSES ONLY, UPON THE EXPRESS CONDITION THAT EACH CUSTOMER SHALL MAKE ITS OWN ASSESSMENT OF APPROPRIATE USE AND APPROPRIATE SHIPPING, TRANSFER AND STORAGE MATERIALS AND PROCEDURES FOR SASOL NORTH AMERICA'S PRODUCTS. ALTHOUGH BASED ON INFORMATION SOURCES WHICH SASOL NORTH AMERICA CONSIDERS ACCURATE AND RELIABLE, SASOL NORTH AMERICA MAKES NO WARRANTY, EITHER EXPRESS OR IMPLIED, INCLUDING ANY WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, REGARDING THE VALIDITY OF THIS INFORMATION, THE INFORMATION SOURCES UPON WHICH THE SAME ARE BASED, OR THE RESULTS TO BE OBTAINED, AND EXPRESSLY DISCLAIMS LIABILITIES FOR DAMAGES OR INJURIES RESULTING FROM THE USE THEREOF.